8 / 16 Port - Combo KVMs

Features

1. Controls 8 or16 computers from a single console (Keyboard/Mouse) over PS/2.
2. Complex connections with PCs via either way of PS/2 and/or USB arbitrarily.
3. Supports Windows, Linux, Mac OS9/OSX, Sun Microsystems.
4. On-Screen-Display (OSD) & Cascade Chain functions.
   - OSD is intuitive menus driven for quick and efficient navigation.
   - 3 level cascades: up to 3 levels; control up to 64/256/4096 PCs, from a single console; cascaded units don't need special configuration.
5. Emulates a keyboard on each PC to allow your computers to boot normally without a keyboard error.
6. Supports hot-pluggable. All devices connected to the KVM can be added or removed at any time, without shutting the unit down.
7. Supports 3 types of switching: (1) Hardware Push Button
   (2) Hot-Keys on PS/2 keyboard
   (3) Menu driven OSD (On Screen Display).
8. Supports Auto-Scan function to switch video automatically among computers in preset intervals sequentially via OSD menus driven.
9. Supports LED display for PC and/or server status monitoring.
10. Supports VGA resolutions up to 2048 x 1536.
11. Supports Beeper during Switching enabled.
12. Powered with external power adaptor connection.
13. Rack Mountable in 19" system tack (1U).

System Requirements

Console

- A VGA, SVGA, Multisync monitor capable of the highest resolution.
- PS/2 - Keyboard/ -Mouse

Computer or Server

The following equipment must be equipped with each computer or server:

- A VGA, SVGA or Multisync card.
- Type A USB port and/or PS/2 6 pin mini-DIN for Keyboard and Mouse.

©2006 All rights reserved

Specification

Number Of Computers Controlled		8 or 16
Selection Method		Hardware Push Button and Hot-Key (PS/2 Keyboard) Or On-Screen-Display (OSD)
LEDs		Red for PC Selection Green for PC On-Line ready
PC Connectors	Video	8 / 16 x HDB-15 female
		(PS/2 & USB signals combined)
Console Ports	Keyboard	1 x 6 pin mini-DIN female
	Mouse	1 x 6 pin mini-DIN female
	Video	1 x HDB-15 female
Auto-Scan Interval		Adjustable time interval setting by OSD menus driven
DDC, DDC2 monitor		Yes (Max. Resolution up to 2048 x1536)
Hot Swappable		Yes
Operating systems supported		Windows 98SE/ME/2000/XP/2003 Server, Linux
		Mac OS9/OSX , SUN.
Device driver		No Need
Power		Powered by external power adaptor
Dimensions (L X W X H)		44 x 15.7 x 4.5 cm (17.3 x 6.1 x 1.5 inch)
Unit Weight		1750g / 1900 g
Housing material		Metal
Operating Temperature		32~ 122°F (0~ 50°C)
Humidity		0%~80%RH

Art.Nr. **DC-13101** EAN-Nr. **4016032200963** Combo-KVM Switch 1User (PS/2), 8PCs (PS/2,USB)
Art.Nr. **DC-14101** EAN-Nr. **4016032200932** Combo-KVM Switch 1User (PS/2), 16PCs (PS/2,USB)

©2006 All rights reserved